

NEW STAKPAK (NSO) SYSTEM STRAIGHT WALL CONTAINERS

SPECIFICATIONS AND PRICING


Model Number	Bottom Style (S) (R)	Containers/Layer 30"x36" 45"x48"	Outside Dimensions				Inside Dimensions				Product Clearance** M' H'	Colors Available:(1) Grey, (2) Medium Green, or (3) Blue		Weight (lbs.) ±3% M R	Volume (cu.ft.) M R	Truckload Quantity 53' Trailer	Available Colors
			Top		Bottom		Top		Bottom			Height'					
			L' W'	L' W'	L' W'	L' W'											
CONTAINERS																	
OR-NSO1207-5	✓ N/A	12	24	120 7.4	120 7.4	9.7 5.8	9.4 5.5	5.0	4.5 N/A	1.1 N/A	0.13 N/A	7,488	1, 2, 3				
OR-NSO1215-4	✓ ✓	6	12	120 15.0	120 15.0	9.7 13.3	9.4 13.0	4.0	3.4 2.9	1.5 2.1	0.25 0.21	6,864	**				
OR-NSO1215-5	✓ ✓	6	12	120 15.0	120 15.0	9.7 13.3	9.4 13.0	5.0	4.4 3.8	1.6 2.2	0.32 0.29	6,240	1, 2, 3				
OR-NSO1215-7	✓ ✓	6	12	120 15.0	120 15.0	9.7 13.3	9.4 13.0	7.5	6.8 6.3	2.2 2.8	0.56 .47	4,056	1, 2, 3				
OR-NSO1215-9	✓ ✓	6	12	120 15.0	120 15.0	9.7 13.3	9.4 13.0	9.5	8.8 8.3	2.5 3.1	0.62 0.62	3,120	1, 2, 3				
OR-NSO1615-7	✓ N/A	9	18	160 15.0	160 15.0	13.3 13.4	13.0 12.9	7.5	6.8 N/A	2.9 N/A	0.68 N/A	3,042	1				
OR-NSO1615-9	✓ N/A	9	18	160 15.0	160 15.0	13.3 13.4	13.0 12.9	9.5	8.8 N/A	3.3 N/A	0.67 N/A	2,340	1				
OR-NSO2415-4	✓ ✓	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	4.0	3.4 2.9	2.6 3.8	0.56 .47	3,900	**				
OR-NSO2415-5	✓ N/A	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	5.0	4.4 N/A	3.0 N/A	0.72 N/A	3,120	1, 2, 3				
OR-NSO2415-7	✓ ✓	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	7.5	6.8 6.3	3.6 4.8	1.09 1.01	2,028	1, 2, 3				
OR-NSO2415-9	✓ ✓	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	9.5	8.8 8.3	4.4 5.0	1.42 1.39	1,560	1, 2, 3				
OR-NSO2415-11	N/A ✓	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	11.0	N/A 9.8	N/A 6.0	N/A 1.67	1,248	**				
OR-NSO2415-11.5	✓ N/A	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	11.5	10.9 N/A	5.0 N/A	1.78 N/A	1,248	1, 2, 3				
OR-NSO2415-14	✓ N/A	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	14.5	13.8 N/A	5.7 N/A	2.20 N/A	936	1, 2, 3				
OR-NSO2422-7	✓ ✓	4	24	22.5 24.0	22.5 24.0	21.7 20.8	21.4 20.5	7.5	6.8 6.3	4.8 6.2	1.78 1.64	1,352	**				
OR-NSO2422-9	✓ N/A	4	24	22.5 24.0	22.5 24.0	21.7 20.8	21.4 20.5	8.7	8.1 N/A	4.9 N/A	2.06 N/A	1,144	1, 2, 3				
OR-NSO2422-11	✓ ✓	4	24	22.5 24.0	22.5 24.0	21.7 20.8	21.4 20.5	10.9	10.4 9.8	6.3 7.8	2.64 2.56	906	1, 2, 3				
OR-NSO2422-14	✓ ✓	4	24	22.5 24.0	22.5 24.0	21.7 20.8	21.4 20.5	14.5	13.8 13.3	7.1 8.5	3.50 3.47	312	1, 2, 3				
CONTAINERS WITH ATTACHED LIDS																	
OR-NBOA1215-7	✓ N/A	6	12	120 15.0	120 15.0	13.3 9.7	13.0 9.4	7.5	6.6 N/A	2.9 N/A	0.48 N/A	3,744	1				
OR-NBOA1215-9	✓ N/A	6	12	120 15.0	120 15.0	13.3 9.7	13.0 9.4	9.5	8.6 N/A	3.2 N/A	0.62 N/A	3,120	**				
OR-NBOA2415-7	✓ N/A	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	7.5	6.6 N/A	5.2 N/A	1.10 N/A	2,028	1				
OR-NBOA2415-9	✓ N/A	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	9.5	8.6 N/A	5.6 N/A	1.43 N/A	1,560	**				
OR-NBOA2415-11.5	✓ N/A	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	11.5	10.8 N/A	6.5 N/A	1.79 N/A	1,248	**				
OR-NBOA2415-14	✓ N/A	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	14.5	13.8 N/A	7.3 N/A	2.28 N/A	936	**				

*Smooth (M) Containers are priced above. Call for pricing on Reinforced (R) Containers. **Please call for pricing. Minimum quantities and set-up charges may apply.
 ✓ = Available • N/A = Not Available • ***When containers are stacked on top of each other, approximately 1/2" is lost to nesting. Example: Bottom container in a stack is 7.5" in height. Containers of the same height stacked on top of it are 7.0" in height. • Outside dimensional tolerance of ±.05".

Call for options such as dunnage, cardholders, label placards, hot stamped logo identification, and pallets and top caps to match your NSO or SO Systems.




Call for custom dunnage options.



Smooth Bottom (M)



Reinforced Bottom (R)



Textured Bottom (S)

STAKPAK (SO) SYSTEM CONTAINERS FOR USE WITH FLOW RACK

SPECIFICATIONS AND PRICING

Model Number	Bottom Style (S) (R)	Containers/Layer 30"x36" 45"x48"	Outside Dimensions				Inside Dimensions				Total Container Height'	Product Clearance ***	Colors Available:(1) Grey, (2) Medium Green, or (3) Blue		Weight (lbs.) ±3%	Volume (cu.ft.)	Truckload Quantity 53' Trailer	Available Colors
			Top		Bottom		Top		Bottom									
			L' W'	L' W'	L' W'	L' W'												
CONTAINERS (Call for pricing and information on Covers)																		
OR-SO1207-5	✓ N/A	12	24	120 7.4	120 7.4	9.7 5.8	9.4 5.5	5.0	4.5	1.3	0.13	7,488	**					
OR-SO1215-5	✓ N/A	6	12	120 15.0	120 15.0	9.7 13.3	9.4 13.0	5.0	4.6	2.1	0.32	5,928	**					
OR-SO2411-9	✓ N/A	8	24	11.2 24.0	11.2 24.0	9.7 9.6	9.4 9.3	9.5	8.7	4.3	1.03	2,080	**					
OR-SO2415-5	✓ N/A	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	5.0	4.5	3.8	0.72	3,120	**					
OR-SO2415-9	✓ N/A	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	9.5	8.8	5.2	1.42	1,560	**					
OR-SO2415-14	N/A ✓	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	14.5	13.3	8.3	2.14	864	**					
OR-SO2422-7	✓ N/A	4	24	22.5 24.0	22.5 24.0	21.7 20.8	21.4 20.5	7.3	6.5	5.5	1.70	1,352	**					
OR-SO2422-9	✓ N/A	4	24	22.5 24.0	22.5 24.0	21.7 20.8	21.4 20.5	8.7	7.9	8.2	2.06	1,144	**					
OR-SO2422-11	✓ N/A	4	24	22.5 24.0	22.5 24.0	21.7 20.8	21.4 20.5	10.9	10.3	7.5	2.64	936	**					
OR-SO3215-7	✓ N/A	4	32	15.0 32.0	15.0 32.0	29.7 13.3	29.4 13.0	7.5	6.7	5.8	1.50	1,352	1, 2, 3					
OR-SO4815-7	N/A ✓	3	48	15.0 48.0	15.0 48.0	45.7 13.3	45.4 13.0	7.5	6.3	8.3	2.30	1,014	1, 2, 3					
OR-SO4815-11	N/A ✓	3	48	15.0 48.0	15.0 48.0	45.7 13.3	45.4 13.0	10.8	9.6	10.1	3.00	624	1, 2, 3					
OR-SO4822-7	N/A ✓	2	48	22.5 48.0	22.5 48.0	45.7 20.8	45.4 20.5	7.3	6.3	9.8	3.00	676	1, 2, 3					
CONTAINERS WITH ATTACHED LIDS																		
OR-SOA2411-9	✓ N/A	8	24	11.2 24.0	11.2 24.0	21.7 9.6	21.4 9.3	9.5	8.5	5.8	2.28	2,080	**					
OR-SOA2415-9	✓ N/A	6	24	240 15.0	240 15.0	21.7 13.3	21.4 13.0	9.5	8.5	7.0	1.40	1,560	**					

✓ = Available • N/A = Not Available • **Please call for pricing. Minimum quantities and set-up charges may apply. • ***When containers are stacked on top of each other, approximately 1/2" is lost to nesting. Example: Bottom container in a stack is 7.5" in height. Containers of the same height stacked on top of it are 7.0" in height. • Outside dimensional tolerance of ±.05".