

TP1800 Locking Pin Swivel Casters



- Made of zinc alloy die cast.
- Designed to prevent problems caused by thread, lint, hair, etc. Wheel disassembles for cleaning.
- Oil-resistant rubber tread
- Used for chairs, dollies, display stands & work aids
- 3" Wheel diameter • Load capacity: 100 lbs.

Top Plate Casters: • O.A. Size: 1 1/2" x 1 1/2" • Hole Spacing: 1 1/2" x 1 1/2" • Attaching Bolt: 1/2"

TO-TP1876-01 O.A. Height: 3 1/2"

Rectangular Plate Casters: • O.A. Size: 1 1/2" x 3" • Hole Spacing: 1/2" x 2 1/2" • Attaching Bolt: 1/2"

TO-TP1876-02 O.A. Height: 3 1/2"

Threaded Stem Casters: (O.A. Height: 2 1/2")

TO-TP1876-21 1/2" dia. x 24 TPI x 1 1/2"

TO-TP1876-22 1/2" dia. x 18 TPI x 1 1/2" • **TO-TP1876-23** 1/2" dia. x 18 TPI x 1 1/2"

TP4000 General Duty Swivel Casters



- Ideal for general duty dollies, platforms, tray racks, etc.
- Zinc plated. • Capacity to 300 lbs.
- Wheel diameters: 3" and 4" (Call for other diameters)
- Large single raceways deeply embossed for strength.
- Special precision king pin engineered for thrust absorption and durability.
- Axle and nut design for wheel assembly (except 1 1/2" is riveted).
- Optional top lock brakes available. • Choice of wheel types. (CALL)

Swivel Model #	Wheel Type	Load Cap.	Bearing Type
TO-TP4000-01-PLY	polyurethane 3" dia.	220 lbs.	ball
TO-TP4000-01-HDP-SLB	hwy. duty plastic 3" dia. w/Side Lock Brake	250 lbs.	plain
TO-TP4000-01-PLY-SLB	polyurethane 3" dia. w/Side Lock Brake	220 lbs.	ball
TO-TP4000-01-HR-SLB	hard rubber 4" dia. w/Side Lock Brake	300 lbs.	nylon

Call for other sizes, capacities, materials and options of casters.

TP5000 Light Medium Duty Swivel Casters



- Ideal for stock carts, bakery racks, & food service.
- Capacity to 350 lbs.
- Wheel diameter: 5"
- Yoke assembly formed from heavily embossed steel.
- 1/2" king pin increases shock absorbing capacity.
- Zinc plated.
- Sealed in raceway helps guard against dust and dirt.
- Optional top lock brakes available. • Other wheel choices available.

Top Plate: • Size: 3 1/2" x 4 1/2" • Hole Spacing: 2 1/2" x 3 1/2" to 3"x3" • Attaching bolt size: 1/2"

Swivel Model #	Wheel Type	Load Cap.	Bearing Type
TO-TP5000-02-PHN	phenolic 5" dia.	350 lbs.	roller
TO-TP5000-02-PLY	polyurethane 5" dia.	250 lbs.	ball
TO-TP5000-02-PHN-TLB	phenolic 5" dia. w/Top Lock Brake	350 lbs.	roller
TO-TP5000-02-PLY-TLB	polyurethane 5" dia. w/Top Lock Brake	250 lbs.	ball

Call for other sizes, capacities, materials and options of casters.

TP6200 Medium Duty Casters



- Ideal for med. duty platform trucks, large stock carts, tray racks and distribution equipment.
- Capacity: 550 lbs. • Wheel diameter: 6"
- Hardened double swivel raceway.
- Grease hole in lower cup. • 2" fork spacing.
- Choice of 2 top plates. • Call for other caster options.

Top Plate: • Size: 4" x 4 1/2" • Hole Spacing: 2 1/2" x 3 1/2" to 3"x3" • Attaching Bolt Size: 1/2"

Model #	Wheel Type	Load Cap.	Bearing Type
TO-TP6200-02-PCI	polyurethane 6" dia.	550 lbs.	roller
TO-TP6200-02-PHN	phenolic 6" dia.	550 lbs.	roller
TO-TP6200-02-PCI-TLB	polyurethane 6" dia. w/Top Lock Brake	550 lbs.	roller
TO-TP6200-02-PHN-TLB	phenolic 6" dia. w/Top Lock Brake	550 lbs.	roller

Kotzin Thread Guard Casters



- Thread deflector prevents threads from tangling around the axle. Keeps wheels operating smoothly and helps with thread removal.
- Useful for light duty applications.
- Double row swivel construction, 1/2" dia. rivet axle.
- Zinc-plated attractive, corrosion-resistant finish.
- Heat treated hardened factory lubricated swivel raceways.
- Wheel Type: Durafoam (Solid) - black molded polypropylene.

Top Plate Casters

• O.A. Size: 2 1/2" x 3 1/2" • Hole Spacing: 1 1/2" x 3" • Hole Dia.: 1 1/2" • Bolt Dia.: 1/2"

TOPPLATESWIVEL Model Number	Wheel Dia.	Tread Width	Capacity (lbs.)	Bearing	Ht. (in.)	Wt. (lbs.)
ER-2F895027081100	3"	1"	125	plain	3 1/2"	1
ER-2F8954027081100	4"	1"	140	plain	4 1/2"	1 1/2
ER-2F8959027081100	5"	1"	145	plain	5 1/2"	1 1/2

TOPPLATE RIGID Model Number	Wheel Dia.	Tread Width	Capacity (lbs.)	Bearing	Ht. (in.)	Wt. (lbs.)
ER-1F833027081100	3"	1"	125	plain	3 1/2"	1
ER-1F8354027081100	4"	1"	140	plain	4 1/2"	1 1/2
ER-1F839027081100	5"	1"	145	plain	5 1/2"	1 1/2

Friction Ring Stem Casters Stem Size: 1/2" dia. x 1 1/2"

SWIVEL FRICTION RING STEM Model Number	Wheel Dia.	Tread Width	Capacity (lbs.)	Bearing	Ht. (in.)	Wt. (lbs.)
ER-2F8953027081101	3"	1"	125	plain	3 1/2"	1 1/2
ER-2F8954027081101	4"	1"	140	plain	4 1/2"	1 1/2
ER-2F8959027081101	5"	1"	145	plain	5 1/2"	1 1/2

Threaded Stem Casters Stem Size: • 1/2" dia. x 18 TPI x 1 1/2"

SWIVEL THREADED STEM Model Number	Wheel Dia.	Tread Width	Capacity (lbs.)	Bearing	Ht. (in.)	Wt. (lbs.)
ER-2F8953027081104	3"	1"	125	plain	3 1/2"	1 1/2
ER-2F8954027081104	4"	1"	140	plain	4 1/2"	1 1/2
ER-2F8959027081104	5"	1"	145	plain	5 1/2"	1 1/2

Call for pricing on these Stem Size Threaded Stem Casters: • 1/2" dia. x 24 TPI x 1 1/2" • 1/2" dia. x 18 TPI x 1 1/2"

TP5200 Light Medium Duty Casters



- Ideal for light-medium material handling equipment, mower's dollies & equipment cases.
- Fully heat treated
- Metal dust cover helps protect swivel raceway
- 1/2" Axle size
- Wheel diameter: 3" or 4"
- Load capacity: 165 - 300 lbs.

Model #	Wheel Type	Load Cap.	Bearing Type
TO-TP5200-01-PLY	swivel polyurethane 3" diameter	220 lbs.	ball
TO-TP5200R-01-PLY	rigid polyurethane 3" diameter	220 lbs.	ball
TO-TP5200-01-SRB	swivel soft rubber 4" diameter	165 lbs.	ball
TO-TP5200-01-HDP	swivel heavy duty plastic 4" diameter	300 lbs.	plain

TP6900 Medium Heavy Duty Casters



- Ideal for large platform trucks, freight terminal trucks, cargo containers, drying racks
- 1/2" nut and bolt king pin
- Legs are machine welded for uniform consistency & strength
- 1/2" diameter axle and lock nut
- Wheel diameter: 6" or 8"
- Load capacity: 1,600 lbs.

Model #	Wheel Type	Load Cap.	Bearing Type
TO-TP6900R-01-PHN	rigid phenolic 6" diameter	1,600 lbs.	roller
TO-TP6900-01-PHN	swivel phenolic 6" diameter	1,600 lbs.	roller
TO-TP6900R-01-PCI	rigid polyurethane 6" diameter	1,600 lbs.	roller
TO-TP6900-01-PCI	swivel polyurethane 6" diameter	1,600 lbs.	roller