

# TT SEMI-AUTOMATIC STRETCH WRAP MACHINE – MODEL SWA-48

- Easy to Operate • 48" Powered Turntable • Capacities Up to 5,000 lbs.

48" Diameter Powered Turntable  
(available in diameters of up to 60")

Model VE-SWA-48

Model  
VE-SWA-48  
shown with  
optional  
approach  
ramp  
VE-SWA-R-4836



115V, 1/2 HP  
Motor



Optional Powered  
Mast - Model #  
VE-SWA-PMO

- Remote foot pedal control
- Variable speed control
- Optional Approach Ramp
- Optional Powered Mast
- Maximum Stretch Wrap Diameter is 11"
- 1/2 HP Drive Motor

## Semi-Automatic Stretch Wrap Machine

Increase productivity in the shipping department or at the end of a production line with the Semi-Automatic Stretch Wrap Machine. This unit is complete with a 48" diameter powered turntable and counter-balanced stretch film mast. Easy to operate, simply depress the foot pedal and manually move the mast up and down. Powered by a 115 V, 1/2 HP motor with soft start / stop and variable speed control. Variable R.P.M 3-12. Unit comes with one film rod with special spacers that can be used with any height roll of stretch wrap material between 10" and 20". Ships knockdown. Some assembly required.

**The Approach Ramp** option allows the operator to load and unload the machine with a pallet truck.

**The Powered Mast** option is available with a 24V hand control to work with those taller loads. The hand held control is used to raise / lower the film while the foot control is used to operate the turntable.

## Semi-Automatic Stretch Wrap Machine -- Specifications & Pricing

Model #	Turntable Dia.	Turntable Ht.	Capacity (lbs.)	Max.Load Dia.	Max.Load Ht.	Net Wt.(lbs.)
VE-SWA-48	48"	2'6"	4,000	76"	76"	665

## Semi-Automatic Stretch Wrap Machine Accessories -- Specifications & Pricing

VE-SWA-PMO	Power Mast Option (Factory Installed)					30
VE-SWA-R-4836*	48"W x 36" L x 2'6"H Approach Ramp (For Electric Pallet Trucks)					223
VE-SWA-R-4848*	48"W x 48" L x 2'6"H Approach Ramp (For Manual Pallet Trucks)					253

\*For use with model VE-SWA-48 only



## TT ELECTRIC HYDRAULIC SCISSOR LIFT TABLES

### Electric Hydraulic Scissor Lift Tables

Full featured electric hydraulic scissor lift tables are used by all types of manufacturing and warehouse facilities. Safety features include: electric toe guard to protect pinch points during lowering of the table, brass velocity fuse to maintain platform height regardless of hydraulic pressure, 24V AC push-button hand control, maintenance prop, and upper travel limit switch to stop table at maximum height reducing motor wear. 2HP, 480V, 3 phase, 60 Hz totally enclosed motor standard, other voltages available. 3000 psi hydraulic component rating.

## Electric Hydraulic Scissor Lift Tables -- Specifications & Pricing

Model #	Platform Size (WxL)	Lowered Ht.	Raised Ht.	Capacity (lbs.)	Voltage Phase	Net Wt.(lbs.)
VE-EHLT-2448-3-43	24"x 48"	7"	43"	3,000	480/3	700
VE-EHLT-4048-3-43	40"x 48"	7"	43"	3,000	480/3	800

## Accessories for Electric Hydraulic Scissor Lift Tables -- Specifications & Pricing

VE-EHLT-SEMI-PO	Semi-Portability Option (Includes two rigid wheels with a two wheel dolly jack)					
VE-EHLT-FULL-PO	Full Portability Option for 3,000 lb. capacity units up to 90" long (includes two rigid & two swivel casters) with a non-removable push handle, reinforced frame and foot operated floor lock					
VE-ACC-4-3-24-48-43-CI	NFFPA-701 Fire Retardant Accordion Skirting - Customer-Installed, includes hardware (24 x 48)					
VE-ACC-4-3-24-48-43-FI	NFFPA-701 Fire Retardant Accordion Skirting - Factory Installed (24 x 48)					
VE-ACC-4-3-40-48-43-CI	NFFPA-701 Fire Retardant Accordion Skirting - Customer-Installed, includes hardware (40 x 48)					
VE-ACC-4-3-40-48-43-FI	NFFPA-701 Fire Retardant Accordion Skirting - Factory Installed (40 x 48)					
Powered Carousel (CA-Series)	Powered carousel electric hydraulic driven, fixed-speed, hand control, min deck size 54" x 54", Max capacity 4,000 lbs. Add 3/4" to lowered height					